



Deep spaders are designed to work the soil to an extra-deep level to produce an even structure.



FarmaX deep spaders are designed for extra-deep soil working and for breaking and mixing hard layers.

Our deep spaders are often used for preparing asparagus fields, vineyards, orchards and sports fields, and are also used in road construction. FarmaX deep spaders are fitted with specially designed blades for perfect soil mixing. The result: an even soil structure to a depth of up to one metre!

Quality and ease of use

FarmaX deep spaders meet the highest quality standards. Thanks to their compact construction and low integral weight, these machines can be used in a three-point hitch. Furthermore, the machines can be supplied with a hydraulically adjustable pressure roller.



Types: DRP-D, LRP-D, LRG-D

Transmission case with differential: as DRP-Perfect and LRP-Profi

Capacity: Up to 0,74 acres (0.3 hectare) per hour in optimum conditions


Tractor power: 160 to 230 HP

Type DRP-D

Specially designed for horticulture, fruit growing, turning over ground for new building and creating plantations. This machine is equipped with a transmission case that can take up to 120 HP and a power take-off thrust of 540 r.p.m. The machine works soil to a depth of 25.59" (65 cm).



Option: Oil cooler



Specially designed digging spades



Can be equipped with a rotary cultivator.



Heavy-duty chain drive

Type LRP-D

Developed for heavier conditions and greater working depth. With a maximum working depth of 33.46" (85 cm), this deep spader creates an even soil structure that increases yield. The LRP-D is fitted with a transmission case that can take up to 200 HP and has a power take-off thrust of 1,000 r.p.m.

Type LRG-D

The heavyweight for the most difficult conditions. This highly robust machine has a maximum working depth of 39.4" (100 cm), is equipped with a transmission case built to take up to 240 HP, and has a power take-off thrust of 1,000 r.p.m.

Advantages

- special blades for excellent mixing to great depths
- optimum, even soil structure
- a good machine for all conditions
- can be used in a three-point hitch
- very user-friendly and easy to maintain

Technical Data

| type | operating width | max. operating depth | standard weight | required power kW/HP | number of spades |
|------------|------------------|----------------------|----------------------|----------------------|------------------|
| DRP-D 160 | 62.99" - 160 cm | 25.59" - 65 cm | 2,094 Lbs - 950 kg | 45/60 | 12 |
| DRP-D 180 | 70.87" - 180 cm | 25.59" - 65 cm | 2,182 Lbs - 990 kg | 48/65 | 15 |
| LRP-D 250 | 98.43" - 250 cm | 33.46" - 85 cm | 4,420 Lbs - 2.005 kg | 82/110 | 18 |
| LRP-D 280 | 110.24" - 280 cm | 33.46" - 85 cm | 4,662 Lbs - 2.115 kg | 103/140 | 18 |
| LRG-D 250 | 98.43" - 250 cm | 33.46" - 85 cm | 6,503 Lbs - 2.950 kg | 103/140 | 18 |
| LRG-D 280 | 110.24" - 280 cm | 33.46" - 85 cm | 6,944 Lbs - 3.150 kg | 110/150 | 24 |
| LRG-DD 250 | 98.43" - 250 cm | 43.31" - 110 cm | 6,944 Lbs - 3.150 kg | 118/160 | 18 |
| LRG-DD 280 | 110.24" - 280 cm | 43.31" - 110 cm | 7,605 Lbs - 3.450 kg | 130/180 | 24 |

SALE ORGANIZATION

Wasse BV
Oranjekanaal Zuidzijde 17
9415 PR Hijken (NL)
Tel: +31 (0)593-524066
Gerry Wasse: +31 (0)6-53428536
sales@farmaxspadingmachine.com

MANUFACTURER

Farmax metaaltechniek BV
Nijverheidsstraat 5
7591 BM Denekamp (NL)
Tel: +31 (0)541-351267
www.farmax.info

FOLLOW US  

YOUR DEALER